

Crushers



This website uses cookies

We use cookies to personalise content and ads, to provide social media features and to analyse our traffic. We also share information about your use of our site with our social media, advertising and analytics partners who may combine it with other information that you've provided to them or that they've collected from your use of their services.

Necessary		
Preferences		
Statistics		
Marketing		
		Show details >
	Allow all	
	Allow selection	
	Deny	
	Powered by Cookiebot by Usercentrics	





This website uses cookies

We use cookies to personalise content and ads, to provide social media features and to analyse our traffic. We also share information about your use of our site with our social media, advertising and analytics partners who may combine it with other information that you've provided to them or that they've collected from your use of their services.

Necessary	
Preferences	
Statistics	
Marketing	
	Show details >
Allow a	all
Allow sele	ection
Deny	,

Powered by Cookiebot by Usercentrics

The swarf loaded in the hopper is dismembered by a hooked arm which performs pre-shredding and conveys the swarf to the actual grinding point. The skein is then shredded and discharged from below.

Where there is a non-shreddable piece that interferes with the process, the machine automatically ejects it through a side container controlled by two air cylinders.

The unit is powered by a 5.5 kW geared motor with chain transmission and clutch.

DIMENSIONS 1300x500x1000H mm		
POWER 5,5 kW		
This website uses cookies		
We use cookies to personalise content and ads, to prove traffic. We also share information about your use of our analytics partners who may combine it with other inform collected from your use of their services.	site with our social media, advertising and	
Necessary		
necessary		
Preferences		
Statistics		
Marketing		
	Show details >	
Allow a	ıll	
Allow selec	ction	
Deny		
Powered by Cookiebot	by Usercentrics	
number, on the type of the 5. The machine can be config 6. The swarf may contain son	ves to be applied to the crusher depend, by shape and swarf jured with different types of knives (slot size) ne sporadic pieces (end of bar, bar headers, machined,) ze, will be crushed or automatically ejected	

Via del Terziario, 20 - 36016 Thiene (VI) Italy Tel. +39 0445 363950 - Fax. +39 0445 386068 p.iva 02290490248

info@famaproject.com

© 2024 Copyright Fama srl - All Rights reserved

This website uses cookies We use cookies to personalise content and ads, to provide social media features and to analyse our traffic. We also share information about your use of our site with our social media, advertising and analytics partners who may combine it with other information that you've provided to them or that they've collected from your use of their services.		
Necessary		
Preferences Statistics		
Statistics		
Marketing		
Show details >		
Allow all		
Allow selection		
Deny		
Powered by Cookiebot by Usercentrics		