



CENTRIFUGES



FC200



DESCRIPTION

The **FC200** centrifuge is a unit suitable for centrifuging metal, ferrous and non-ferrous swarf, in order to recover the cooling lubricant used by the machine tool in the production process.

The FC200 centrifuge is designed for continuous feeding and for the treatment of short swarf, not exceeding 2 cm in length.

Under optimal conditions, the FC200 centrifuge allows to obtain swarf with a wet content that can reach up to 1.5%.

The actual efficiency of the centrifuge, as well as the hourly flow rate, depends on the characteristics of the swarf, in particular the material, the shape, the weight per unit of volume, as well as the starting humidity and can be confirmed by testing your swarf at our premises. If there are pieces in the swarf, such as bar headers, semi-finished products or bar ends, the FC200 centrifuge should be equipped with a sieve.

Residual swarf moisture after centrifugation can be confirmed by testing your swarf sample

SUPPLY

- The structure is made of sturdy painted metalwork RAL 7016, anchored to a thick and rigid platform;
- All parts in contact with the swarf are made of special wear-resistant materials;
- Discharge channel;
- Vibration dampers to reduce vibrations;
- Discharge of the recovered coolant;
- Washing inlet tap;
- Centrifuge washing pump;
- Recovered coolant drain pipe with a standard length of 1 m;
- Electrical junction box and wiring.

OPTIONAL

- Customised support structure made of sturdy painted metalwork to be anchored to the floor;
- Painting in RAL different from the standard;
- Coolant collection tank with level sensors and 0.3 bar transfer pump;
- Electrical control panel.

HOURLY PRODUCTION

Q = 150 l/h	BRASS	STEEL	ALUMINIUM	STAINLESS STEEL	COPPER	CAST IRON
D density [kg/l]	1.3	1.2	0.4	1	0.8	1.3
Kg/h	200	180	60	150	120	200

THE DATA IN kg/h IS APPROXIMATE AND IN ANY CASE DEPENDS ON THE DENSITY OF THE SWARF, THE SHAPE, THE OIL CONTENT AND THE TYPE OF COOLANT. THE DENSITY DATA CONSIDERED ARE HYPOTHETICAL, BASED ON AN EXPERIMENTAL AVERAGE OF THE DATA IN OUR POSSESSION.

FAMA SRL

Uffici e Produzione /Offices and production site: Via del Terziario, 20 36016 THIENE (VI) ITALY – Tel.+39 0445 363950fax +39 0445 386068

sede Legale/ Registered office: Via S. Antonio,11 -- 36030 FARA VICENTINO (VI) Tax Code/VAT No: IT 02290490248


Cap. Soc. € 100.000,00 R.E.A. VI 220095 <http://www.famaproject.com> e-mail info@famaproject.com Last modification: 13/09/2019



SWARF CHARACTERISTICS & TECHNICAL NOTES

- The swarf must be short or not larger in size than 2 x 1 or 2 cm;
- The swarf must not contain pieces (end of bar, bar headers, processed parts, ...). Pieces in the order of cm are tolerated;
- The centrifuge must be loaded continuously and uniformly to ensure maximum performance;
- A minimum washing flow rate must always be guaranteed, to avoid deposits and clogging.

DIMENSIONS	Ø570 X 600 mm
WEIGHT	100 kg
POWER	0,98 kW
VOLTAGE	230/400 V
POWER SUPPLY	continuous
RPM	2.950 rpm



APPLICATION ANALYSIS EXAMPLE

A WET RESIDUE OF 2% WAS OBTAINED ON A 200 KG SAMPLE OF BRASS WITH A 15% WET CONTENT. 26 KG OF OIL WERE RECOVERED IN 1 HOUR. ASSUMING WORKING 8 HOURS A DAY, FOR 220 DAYS OF THE YEAR, THE FOLLOWING AMOUNT WILL BE RECOVERED: 45,760 KG OF OIL PER YEAR.

FAMA RESERVES THE RIGHT TO MAKE CHANGES TO THE PRODUCT WITHOUT NOTICE

FAMA SRL

Uffici e Produzione /Offices and production site: Via del Terziario, 20 36016 THIENE (VI) ITALY – Tel.+39 0445 363950fax +39 0445 386068
 sede Legale/ Registered office: Via S. Antonio,11 -- 36030 FARA VICENTINO (VI) Tax Code/VAT No: IT 02290490248
 Cap. Soc. € 100.000,00 R.E.A. VI 220095 <http://www.famaproject.com> e-mail info@famaproject.com Last modification: 13/09/2019